



Model	XMS-1808-i3200/G5/G6(1-8)					
Appearance	grey					
Rail	Single rail					
Color	water-baesd/Sublimation/eco					
Printing Speed(sqm/h)	No UV			UV		
	i3200-E12pcs	i3200-E14pcs	F10804pcs	i3200-U12pcs	i3200-U14pcs	F10804pcs
	2pass:60m ² /h	2pass:75m ² /h	2pass:65m ² /h	6pass:24m ² /h	6pass:46m ² /h	6pass:20m ² /h
	4pass:40m ² /h	4pass:50m ² /h	4pass:30m ² /h	8pass:18m ² /h	8pass:36m ² /h	8pass:15m ² /h
Print width (mm)	1800mm					
Print Thickness(mm)	0.1~175mm					
Curing System	LED UVLight(optional)					
Image Format	TIFF/JPG/EPS/PDF/BMP					
Rip Software	PHOTOPRINT/Maintop/Riin Rip-honson					
Applied Materials	PP paper,photo paper,heat transfer paper,back glue,light film,car sticker, spray painting cloth,hot stamping film,etc					
Power Supply	AC220V50HZ ± 10%					
Temperature	20-30°C					
Humidity	50-65%					
Power	5000W External drying 1200W					
Appearance Size(mm)	Length/width/height:3990/1500/1450					
Wooden box size(mm)	Length /width /height:4090/1600/1550					
Net Weight	450kg			Grossweight	500kg	
Data Transmission	TCP/IP network interface					